



MAGNETICALLY OPERATED SWITCHES

FOR GRIPPERS

MODELS	Type	Voltage V d.c.	Current max.	Temperature °C	LED	Signal output	Cable length	Cable type	Straight cable connection	90° elbow cable connection	
	M/344/EAU/1APV	2-wire solid state	10 ... 28	20 mA	0 ... +60	•	-	1 m	PVC	-	•
	M/344/EAU/1PV	2-wire solid state	10 ... 28	20 mA	0 ... +60	•	-	1 m	PVC	•	-
	M/344/EAU/3APV	2-wire solid state	10 ... 28	20 mA	0 ... +60	•	-	3 m	PVC	-	•
	M/344/EAU/3PV	2-wire solid state	10 ... 28	20 mA	0 ... +60	•	-	3 m	PVC	•	-
	M/344/EAN/1APV	3-wire solid state	4,5 ... 28	50 mA	0 ... +60	•	NPN	1 m	PVC	-	•
	M/344/EAN/1PV	3-wire solid state	4,5 ... 28	50 mA	0 ... +60	•	NPN	1 m	PVC	•	-
	M/344/EAN/3APV	3-wire solid state	4,5 ... 28	50 mA	0 ... +60	•	NPN	3 m	PVC	•	•
	M/344/EAN/3PV	3-wire solid state	4,5 ... 28	50 mA	0 ... +60	•	NPN	3 m	PVC	•	-

FOR MINIATURE AND COMPACT ROTARY ACTUATORS

MODELS	Type	Voltage V d.c.	V a.c.	Current max.	Temperature °C	LED	Signal output	Cable length	Cable type	Straight cable connection	90° elbow cable connection	
	M/346/LAU/1PV	Reed	12 ... 100	12 ... 125	40 mA	-10 ... +60	•	-	1,5 m	PVC	-	•
	M/346/LAU/5PV	Reed	12 ... 100	12 ... 125	40 mA	-10 ... +60	•	-	5 m	PVC	-	•
	M/346/EAU/1APV	2-wire solid state	4,5 ... 28	-	70 mA	-10 ... +60	•	-	1,5 m	PVC	-	•
	M/346/EAU/5APV	2-wire solid state	4,5 ... 28	-	70 mA	-10 ... +60	•	-	5 m	PVC	-	•
	M/345/EAU/1PV	2-wire solid state	10 ... 28	-	40 mA	0 ... +60	•	-	1 m	PVC	•	-
	M/345/EAU/3PV	2-wire solid state	10 ... 28	-	40 mA	0 ... +60	•	-	3 m	PVC	•	-
	M/345/EAN/1PV	3-wire solid state	4,5 ... 28	-	100 mA	0 ... +60	•	NPN	1 m	PVC	•	-
	M/345/EAN/3PV	3-wire solid state	4,5 ... 28	-	100 mA	0 ... +60	•	NPN	3 m	PVC	•	-

DIRECT MOUNTED SWITCHES

						
Ø 8 ... 50 mm	Ø 8 ... 50 mm	Ø 8 & 12 mm	Ø 12 ... 25 mm	Ø 16 & 20 mm	Ø 12 ... 20 mm	Ø 14 ... 22 mm
M/1603**/M/11	M/1603**/M/12	M/160360/M/12	M/160390/M/12	M/160380/M/12	M/60210/M	M/60270/M