


RA/28000; .../M, RA/28300; .../M
Pneumatic cylinder, ISO 15552
Non-magnetic & magnetic piston, single acting
Ø 32 ... 100 mm

High performance, stability and reliability

Cylinders and mountings conform to ISO 15552
 (ISO 6431, VDMA 24562 and NFE 49-003-1)

Comprehensive range of mountings

Polyurethane seals ensure efficient low friction operation and long life



Technical features

Medium:

Compressed air, filtered, lubricated or non-lubricated

Standard:

ISO 15552

Note: all models conform to the mentioned standards except the cylinder size

Operation:

RA/28000: Single acting, sprung in, non-magnetic piston and adjustable cushioning

RA/28000/M: Single acting, sprung in, magnetic piston and adjustable cushioning

RA/28300: Single acting, sprung out, non-magnetic piston and adjustable cushioning

RA/28300/M: Single acting, sprung out, magnetic piston and adjustable cushioning

Operating pressure:

2 ... 10 bar

Air ports:

G1/8 ... G1/2

Cylinder diameters:

32, 40, 50, 63, 80, 100 mm

Strokes:

See table below

Non-standard strokes:

Available 250 mm max.

Operating temperature:

-20 ... +80°C max.

Air supply must be dry enough to avoid ice formation at temperatures below +2°C.

Materials:

Barrel:

anodised aluminium,

End covers: pressure diecast aluminium

Piston rod: stainless steel (martensitic)

Piston rod seals: PUR

Piston seals: PUR

O-rings: NBR

Technical data









Cylinder Ø (mm)	32	40	50	63	80	100
Air ports	G 1/8	G 1/4	G 1/4	G 3/8	G 3/8	G 1/2
Piston rod Ø (mm)	12	16	20	20	25	25
Piston rod thread	M10 x 1,25	M12 x 1,25	M16 x 1,5	M16 x 1,5	M20 x 1,5	M20 x 1,5
Cushion length (mm)	19	22	24	24	27	34
Initial cushion volume (cm³)	12,3	20,7	36	64	116	242
Air consumption at 6 bar outstroke (l/cm)	0,056	0,088	0,137	0,218	0,35	0,55
Air consumption at 6 bar instroke (l/cm)	0,048	0,074	0,114	0,195	0,32	0,51
RA/28000/M, RA/28000 (28100)						
Theoretical thrusts at 6 bar outstroke (N)	392	648	1043	1735	2795	4492
F1 (N)	50	60	75	75	130	130
RA/28300/M, RA/28300						
Theoretical thrusts at 6 bar instroke (N)	324	528	854	1546	2501	4197
F1 (N)	50	60	75	75	130	130

F1 = Final return force of spring

Standard strokes

Cylinder Ø (mm)	Stroke length (mm)			
	25	50	80	100
32	•	•	•	•
40	•	•	•	•
50	•	•	•	•
63	•	•	•	•
80	•	•	•	•
100	•	•	•	•

Cylinder variants

Symbol	Model Non-magnetic piston		Symbol	Model magnetic piston		Description	Dimensions
	C	S		C	S		
	•	•		•	•	Standard cylinder, sprung in	6
						Cylinder with special wiper/seal, suitable for applications with arizona sand, cement, plaster (stucco), hoar-frost or ice	
						Cylinder with non-rotating piston rod	7
	•	•		•	•	Standard cylinder, sprung out	6
						Cylinder with special wiper/seal, suitable for applications with arizona sand, cement, plaster (stucco), hoar-frost or ice	
						Cylinder with non-rotating piston rod	6

For the cylinder models style C and S see options selector

Option selector


★A/28★/★/★/★/★

Piston rod material	Substitute
Stainless steel martensitic	R
Hard chromium plated	C
Stainless steel austenitic	S
Operation	Substitute
Sprung in (Ø 32 ... 80 mm)	0
Sprung in (Ø 100 mm only)	1
Sprung out	3
Cylinder Ø	Substitute
32	32
40	40
50	50
63	63
80	80
100 (Sprung out)	10
100 (Sprung in)	00

Strokes (mm)	Substitute
250 max.	
Variants (magnetic piston)	Substitute
Standard	M
Non-rotating piston rod	N2
Special wiper/seal	W2
Variants (non-magnetic piston)	Substitute
Standard	None
Non-rotating piston rod	N1
Special wiper/seal	W1

Note: If option is not required, disregard option position within part number eg. RA/28100/M/50. For combinations of cylinder variants consult our Technical Service. This options selector explains only the cylinder variants. Additional variants/options are not possible.

Mountings



Mountings

Model	A	AK	B, G	C	D	D2	F	FH	H
Cyl. Ø	10 Page 8	18 Page 8	1 Page 8	2 Page 8	5 Page 8	8 Page 8	15 Page 9	9 Page 9	11 Page 9
32	QM/8032/35	QM/8025/38	QA/8032/22	QA/8032/21	QA/8032/23	QA/8032/42	QM/8025/25	QA/8032/34	QA/8032/28
40	QM/8032/35	QM/8040/38	QA/8040/22	QA/8040/21	QA/8040/23	QA/8040/42	QM/8040/25	QA/8040/34	QA/8040/28
50	QM/8050/35	QM/8050/38	QA/8050/22	QA/8050/21	QA/8050/23	QA/8050/42	QM/8050/25	QA/8050/34	QA/8050/28
63	QM/8050/35	QM/8050/38	QA/8063/22	QA/8063/21	QA/8063/23	QA/8063/42	QM/8050/25	QA/8063/34	QA/8063/28
80	QM/8080/35	QM/8080/38	QA/8080/22	QA/8080/21	QA/8080/23	QA/8080/42	QM/8080/25	QA/8080/34	QA/8080/28
100	QM/8080/35	QM/8080/38	QA/8100/22	QA/8100/21	QA/8100/23	QA/8100/42	QM/8080/25	QA/8100/34	QA/8100/28

	R	S	SS	SW	UF	UH	UR	US
Cyl. Ø	3 Page 10	12 Page 10	16 Page 11	6 Page 10	17 Page 10	11 Page 9	4 Page 10	7 Page 11
32	QA/8032/27	QA/8032/41	M/P19931	M/P19493	QM/8025/32	PQA/182032/40	QA/8032/33	M/P40310
40	QA/8040/27	QA/8040/41	M/P19932	M/P19494	QM/8040/32	PQA/182040/40	QA/8040/33	M/P40311
50	QA/8050/27	QA/8040/41	M/P19933	M/P19495	QM/8050/32	PQA/182050/40	QA/8050/33	M/P40312
63	QA/8063/27	QA/8063/41	M/P19934	M/P19496	QM/8050/32	PQA/182063/40	QA/8063/33	M/P40313
80	QA/8080/27	QA/8063/41	M/P19935	M/P19497	QM/8080/32	PQA/182080/40	QA/8080/33	M/P40314
100	QA/8100/27	QA/8100/41	M/P19936	M/P19498	QM/8080/32	PQA/182100/40	QA/8100/33	M/P40315

Accessories

Magnetically operated switches

	M/50/**	Switch mounting brackets for M/50	TQM/31, QM/32, QM/132	Switch mounting brackets for TQM/31, QM/32, QM/132	QM/140	Switch mounting brackets for QM/140
Cyl. Ø	Page 12 + 13	23 Page 13	Page 14	Page 14	Page 15	Page 15
32		QM/27/2/1		QM/31/032/22		QM/140/010/22
40		QM/27/2/1		QM/31/032/22		QM/140/010/22
50		QM/27/2/1		QM/31/032/22		QM/140/010/22
63		QM/27/2/1		QM/31/032/22		QM/140/010/22
80		QM/27/2/1		QM/31/080/22		QM/140/010/22
100		QM/27/2/1		QM/31/080/22		QM/140/010/22

Service kit


	Service kit
Cyl. Ø	
32	QA/8032/00
40	QA/8040/00
50	QA/8050/00
63	QA/8063/00
80	QA/8080/00
100	QA/8100/00

Basic dimensions
RA/28000, RA/28000/M
Standard cylinder

Sprung in

RA/28300, RA/28300/M
Standard cylinder

Sprung out





Ø	AM	AP	Ø Be 11	Ø BAe ¹¹	BG	BH	q E	EE	G	KK	KV	
32	22	3,5	30	30	16	6	47	G 1/8	27,5	M10x1,25	17	
40	24	4,5	35	35	16	6	53	G 1/4	32	M12x1,25	19	
50	32	6	40	40	16	8	65	G 1/4	31	M16x1,5	24	
63	32	10	45	45	16	8	75	G 3/8	33	M16x1,5	24	
80	40	8,5	45	45	17	19	95	G 3/8	33	M20x1,5	30	
100	40	9	55	55	17	19	115	G 1/2	37	M20x1,5	30	
Ø	KW	L2	L8	L9	L12	Ø MMh ⁹	PL	q R	RT	SW	VA	
32	5	20	94	4	6	12	13	32,5	M 6	10	3	
40	6	22	105	4	6,5	16	15	38	M 6	13	3,5	
50	8	27	106	5	8	20	18,5	46,5	M 8	17	3,5	
63	8	29	121	5	8	20	19	56,5	M 8	17	4	
80	10	33	128	-	10	25	19	72	M 10	22	4	
100	10	36	138	-	10	25	18	89	M 10	22	4	
Ø	VD	WH	at 0 mm		per 25 mm		Model			Model		
							Non-magnetic piston			Magnetic piston		
32	6	26	0,51 kg		0,06 kg		RA/28#32/*			RA/28#32/M/*		
40	6	30	0,80 kg		0,08 kg		RA/28#40/*			RA/28#40/M/*		
50	6	37	1,33 kg		0,12 kg		RA/28#50/*			RA/28#50/M/*		
63	6	37	1,80 kg		0,13 kg		RA/28#63/*			RA/28#63/M/*		
80	6	46	3,25 kg		0,20 kg		RA/28#80/*			RA/28#80/M/*		
100	6	51	4,81 kg		0,23 kg		RA/28100/* or RA/28310/*			RA/28100/M/* or RA/28310/M/*		
28032	28332	28040	283040	28050	28350	28063	28363	28080	28380	28100	28310	Model
25, 50	80, 100	25, 50	80, 100	25, 50	80, 100	25, 50	80, 100	25, 50	80, 100	25, 50	80, 100	Standard strokes
119	147	130	158	131	159	146	174	153	181	163	191	L8
119 + (N * x 28)	130 + (N * x 28)	131 + (N * x 28)	146 + (N * x 28)	153 + (N * x 28)	163 + (N * x 28)							L8
250 mm max.												non-standard strokes

* Stroke < 50 mm N = 0
Stroke > 50 mm N = $\frac{\text{Stroke} - 1}{50}$ (round up to integer)

Please insert number of spring in (0) or spring out (3).

Cylinder variants
RA/28.00/N1, RA/28.00/N2 – Cylinder with non-rotating piston rod

∅		Torque max (Nm)	Model Non-magnetic piston	Model Magnetic piston
32	10	0,5	RA/28#32/N1/*	RA/28#32/N2/*
40	13	1	RA/28#40/N1/*	RA/28#40/N2/*
50	16	1,5	RA/28#50/N1/*	RA/28#50/N2/*
63	16	1,5	RA/28#63/N1/*	RA/28#63/N2/*
80	16	2,5	RA/28#80/N1/*	RA/28#80/N2/*
100	21	2,5	RA/28100/N1/* or RA/28310/N1/*	RA/28100/N2/* or RA/28310/N2/*




* Please insert standard stroke length.

Please insert number of spring in (0) or spring out (3).

Mountings


Front or rear stud mounting A

Conforms to ISO 15552, type MX1



∅	BB	DD	TG	kg	Model (A)
32/40	17	M6	32,5/38	0,02	QM/8032/35
50/63	23	M8	46,5/56,5	0,05	QM/8050/35
80/100	28	M10	72/89	0,08	QM/8080/35


Piston rod swivel AK



∅	KK	B1	F	L	L2	1	2	3	4	kg	Model (AK)
32	M10x1,25	5	26	73	20	19	12	17	30	0,20	QM/8025/38
40	M12x1,25	6	26	77	24	19	12	19	30	0,20	QM/8040/38
50/63	M16x1,5	8	34	106	32	30	19	24	42	0,65	QM/8050/38
80/100	M20x1,5	10	42	122	40	30	19	30	42	0,72	QM/8080/38

Front flange B, G


Conforms to ISO 15552, type MF1 and MF2



∅	E	∅ FB	MF	R	TF	UF	kg	Model (B, G)
32	50	7	10	32	64	80	0,25	QA/8032/22
40	55	9	10	36	72	90	0,35	QA/8040/22
50	65	9	12	45	90	110	0,70	QA/8050/22
63	75	9	12	50	100	125	0,80	QA/8063/22
80	100	12	16	63	126	154	1,35	QA/8080/22
100	120	14	16	75	150	186	2,20	QA/8100/22

Foot mounting C


Conforms to ISO 15552, type MS1



∅	∅ AB	AH	AO	AT	AU	E	TR	kg	Model (C)
32	7	32	8	4	24	48	32	0,15	QA/8032/21
40	10	36	9	4	28	53	36	0,18	QA/8040/21
50	10	45	10	5	32	64	45	0,30	QA/8050/21
63	10	50	12	5	32	74	50	0,39	QA/8063/21
80	12	63	19	5	41	98	63	0,80	QA/8080/21
100	14	71	19	5	41	115	75	0,95	QA/8100/21

Rear clevis D


Conforms to ISO 15552, type MP2



∅	CB H14	∅ EK f8	FL	L	LH	MR	UB	kg	Model (D)
32	26	10	22	13	52	9	45	0,11	QA/8032/23
40	28	12	25	16	60	12	52	0,16	QA/8040/23
50	32	12	27	17	68	12	60	0,22	QA/8050/23
63	40	16	32	22	79	15	70	0,34	QA/8063/23
80	50	16	36	22	99	15	90	0,54	QA/8080/23
100	60	20	41	27	119	20	110	0,90	QA/8100/23

Rear clevis D2


Conforms to ISO 15552, type AB6



∅	B1 H14	B2	B3	∅ EK h9	FL	R1	R2	kg	Model (D2)
32	14	34	3,3	10	22	11	17	0,20	QA/8032/42
40	16	40	4,3	12	25	12	20	0,23	QA/8040/42
50	21	45	4,3	16	27	14,5	22	0,36	QA/8050/42
63	21	51	4,3	16	32	18	25	0,55	QA/8063/42
80	25	65	4,3	20	36	22	30	0,90	QA/8080/42
100	25	75	4,3	20	41	22	32	1,45	QA/8100/42


Piston rod clevis F

Conforms to DIN ISO 8140



Ø	KK	CE	Ø CK _{h11}	CL	CM	ER	LE	RK	kg	Model (F)
32	M10x1,25	40	10	20	10	16	20	28	0,09	QM/8025/25
40	M12x1,25	48	12	24	12	19	24	32	0,13	QM/8040/25
50/63	M16x1,5	64	16	32	16	25	32	41,5	0,33	QM/8050/25
80/100	M20x1,5	80	20	40	20	32	40	50	0,67	QM/8080/25


Front or rear detachable trunnion FH

 Conforms to VDMA 24562 part 2,
type MT 5/6



Ø	Ø Dh11	L1	R	Ø TDe9	TL	TM _{h14}	UW1	kg	Model (FH)
32	30	16	1	12	12	50	45	0,20	QA/8032/34
40	35	20	1,6	16	16	63	55	0,38	QA/8040/34
50	40	24	1,6	16	16	75	65	0,60	QA/8050/34
63	45	24	1,6	20	20	90	75	1,10	QA/8063/34
80	45	28	1,6	20	20	110	100	1,90	QA/8080/34
100	55	38	2	25	25	132	120	3,50	QA/8100/34

Centre trunnion - H

Conforms to ISO 15552, type MT4


Adjustable trunnion mounting UH

Conforms to ISO 15552, type MT4


3 Locking screws

 Torque max: Ø 32 & 40 mm = 6 Nm; Ø 50 & 63 mm = 10 Nm;
Ø 80 & 100 mm = 15 Nm

Ø	L	R	Ø TD _{e9}	TL	TM _{h14}	UW	XV min.	XV max.	kg	Model (H)
32	20	1	12	12	50	50	66	80	0,16	QA/8032/28
40	24	1,6	16	16	63	58	76	89	0,35	QA/8040/28
50	28	1,6	16	16	75	70	82	98	0,65	QA/8050/28
63	28	1,6	20	20	90	80	88	107	0,85	QA/8063/28
80	28	1,6	20	20	110	100	97	123	1,2	QA/8080/28
100	38	2	25	25	132	126	112	128	2,3	QA/8100/28


Note: Style 'H': These mountings are only supplied assembled complete with the cylinder. Unless otherwise specified, units will be supplied with dimension 'XV' plus half the stroke length. 'XV' = Distance from the piston rod shoulder to the centre of the mounting.

Ø	L	R	Ø TD _{e9}	TL	TM _{h14}	UW	XV min.	XV max.	kg	Model (UH)
32	20	1	12	12	50	50	66	80	0,16	QA/8032/40
40	24	1,6	16	16	63	58	76	89	0,35	QA/8040/40
50	28	1,6	16	16	75	70	82	98	0,65	QA/8050/40
63	28	1,6	20	20	90	80	88	107	0,85	QA/8063/40
80	28	1,6	20	20	110	100	97	123	1,2	QA/8080/40
100	38	2	25	25	132	126	112	128	2,3	QA/8100/40

Style 'UH': It is most important that the locking screws which secure the mounting to the tie rod are tightened to the torque figures shown in the table below. For maximum energy input, consult our Technical Service. Unless otherwise specified, units will be supplied with dimension 'XV' plus half the stroke length. 'XV' = Distance from the piston rod shoulder to the centre of the mounting.

Rear eye R


Conforms to ISO 15552, type MP4



∅	∅ CD _{H9}	EW	FL	L	MR	kg	Model (R)
32	10	25,8	22	13	9	0,09	QA/8032/27
40	12	27,8	25	16	12	0,11	QA/8040/27
50	12	31,7	27	17	12	0,17	QA/8050/27
63	16	39,7	32	22	15	0,24	QA/8063/27
80	16	49,7	36	22	15	0,37	QA/8080/27
100	20	59,7	41	27	20	0,59	QA/8100/27

Trunnion support S


Conforms to ISO 15552, type AT4



∅	A	B1	B2	C	∅ D1H7	∅ D2	∅ D3	Fx 45°	H1	H2	T1	kg	Model (S)
32	32	46	18	10,5	12	6,6	11	1	30	15	6,8	0,10	QA/8032/41
40/50	36	55	21	12	16	9	15	1,6	36	18	9	0,14	QA/8040/41
63/80	42	65	23	13	20	11	18	1,6	40	20	11	0,18	QA/8063/41
100	50	75	28,5	16	25	14	20	2	50	25	13	0,34	QA/8100/41

Universal piston rod eye UF


Conforms to DIN ISO 8139



∅	Thread KK	AX	CE	∅ CN _{H7}	EN-0,1	ER	LE	Z	kg	Model (UF)
32	M10x1,25	20	43	10	14	14	15	13°	0,09	QM/8025/32
40	M12x1,25	22	50	12	16	16	17	13°	0,13	QM/8040/32
50/63	M16x1,5	28	64	16	21	21	22	15°	0,33	QM/8050/32
80/100	M20x1,5	33	77	20	25	25	26	15°	0,67	QM/8080/32

Universal rear eye UR


Conforms to ISO 15552, type MP6



∅	∅ CN _{H7}	EN	ER	FL	R	Z	kg	Model (UR)
32	10	14	16	22	14,5	13°	0,15	QA/8032/33
40	12	16	18	25	18	13°	0,25	QA/8040/33
50	16	21	21	27	19	15°	0,40	QA/8050/33
63	16	21	23	32	24	15°	0,55	QA/8063/33
80	20	25	28	36	24	15°	0,90	QA/8080/33
100	20	25	30	41	29	15°	1,50	QA/8100/33


Wide hinge SW

Conforms to ISO 15552, type AB7



∅	CA	∅ CK _{H9}	∅ D	H2	EM	G1	G2	G3	K1	K2	L1	R	∅ S	kg	Model (SW)
32	32	10	11	7	25,5	21	18	31	38	50	1,6	10	6,6	0,05	M/P19493
40	36	12	11	9	27,5	24	22	35	41	54	1,6	11	6,6	0,07	M/P19494
50	45	12	15	11	31,5	33	30	45	50	65	1,6	13	9	0,14	M/P19495
63	50	16	15	12	39,5	37	35	50	52	67	1,6	15	9	0,18	M/P19496
80	63	16	18	14	49,5	47	40	60	66	84	2,5	15	11	0,28	M/P19497
100	71	20	18	15	59,5	55	50	70	76	94	2,5	19	11	0,42	M/P19498


Narrow hinge SS



Ø	CA	Ø CN ₆₇	Ø D	H2	EM	G1	G2	G3	K1	K2	L1	R	Ø S	kg	Model (SS)
32	32	10	11	8	10	21	18	31	38	51	1,6	10	6,6	0,15	M/P19931
40	36	12	11	10	12	24	22	35	41	54	1,6	11	6,6	0,20	M/P19932
50	45	16	15	12	16	33	30	45	50	65	1,6	13	9	0,48	M/P19933
63	50	16	15	12	16	37	35	50	52	67	1,6	15	9	0,50	M/P19934
80	63	20	18	14	20	47	40	60	66	86	2,5	15	11	0,75	M/P19935
100	71	20	18	15	20	55	50	70	76	96	2,5	19	11	1,20	M/P19936

Swivel hinge US

Conforms to VDMA 24562 part 2



Ø	CH	Ø CN _{H7}	Ø D	EN -0,1	ER	EU	G1	G2	G3	H2	K1	K2	L1	Ø S	Z	kg	Model (US)
32	32	10	11	14	16	10,5	21	18	31	10	38	51	1,6	6,6	13°	0,19	M/P40310
40	36	12	11	16	18	12	24	22	35	10	41	54	1,6	6,6	13°	0,24	M/P40311
50	45	16	15	21	21	15	33	30	45	12	50	65	1,6	9	13°	0,46	M/P40312
63	50	16	15	21	23	15	37	35	50	12	52	67	1,6	9	15°	0,59	M/P40313
80	63	20	18	25	28	18	47	40	60	14	66	86	2,5	11	15°	1,03	M/P40314
100	71	20	18	25	30	18	55	50	70	15	76	96	2,5	11	15°	1,40	M/P40315
125	90	30	20	37	40	25	70	60	90	20	94	124	3,2	14	15°	3,10	M/P71355

Technical data - Reed switches - additional informations see data sheet N/en 4.3.005


Symbol	Voltage (V a.c.)	Voltage (V d.c.)	Current max. (mA)	Function	Temperature (°C)	LED	Protection class	Features	Cable length (m)	Cable type	Weight (g)	Model
	10 ... 240	10 ... 170	180	Closer	-25 ... +80	•	IP66	—	2, 5 or 10	PVC 2 x 0,25	37	M/50/LSU/*V
	10 ... 240	10 ... 170	180	Closer	-25 ... +80	•	IP66	—	5	PUR 2 x 0,25	37	M/50/LSU/5U
	10 ... 240	10 ... 170	180	Closer	-25 ... +150	—	IP66	—	2	Silicon 2 x 0,25	37	TM/50/RAU/2S
	10 ... 240	10 ... 170	180	Changeover	-25 ... +80	—	IP66	—	5	PVC 3 x 0,25	37	M/50/RAC/5V
	10 ... 60	10 ... 60	180	Closer	-25 ... +80	•	IP66	Plug M8 x 1	0,3	PVC 3 x 0,25	16	M/50/LSU/CP *1)

* Insert cable length; *1) Plug-in connector see page 11; Color code: BK = black, BN = brown, BU = blue

Dimensions

M/50/LSU/*V, M/50/LSU/5U, TM/50/RAU/2S


Cable length L = 2, 5 or 10 m



- 1 Fixing screw
- 2 + BN = brown
- BU = blue
(output)



M/50/RAC/5V

Cable length L = 5 m



- 1 Fixing screw
- 2 - BK = black
+ BN = brown
- ≠BU = blue

M/50/LSU/CP



Accessories

Plug-in connector cable with nut






Outer cover	Cable length	Weight (kg)	Connector	Model
PVC 3 x 0,25	5 m	0,18	M8 x 1	M/P73001/5
PUR 3 x 0,25	5 m	0,18	M8 x 1	M/P73002/5
PUR 3 x 0,34	5 m	0,21	M12 x 1	M/P34594/5

Technical data - Solid state - additional informations see data sheet N/en 4.3.007

Symbol	Voltage (V d.c.)	Current max. (mA)	Function	Temperature (°C)	LED	Protection class	Features	Cable length (m)	Cable type	Weight (g)	Model
	10 ... 30	150	PNP	-40 ... +80	•	IP67	—	2, 5 or 10	PVC 3 x 0,12	37	M/50/EAP/*V
	10 ... 30	150	PNP	-40 ... +80	•	IP68	—	5	PUR 3 x 0,14	37	M/50/EAP/5U
	10 ... 30	150	PNP	-40 ... +80	•	IP67	Plug M8 x 1	0,3	PVC 3 x 0,14	16	M/50/EAP/CP *1)
	10 ... 30	150	PNP	-40 ... +80	•	IP67	Plug M12 x 1	0,3	PVC 3 x 0,14	16	M/50/EAP/CC *1)
	10 ... 30	150	NPN	-40 ... +80	•	IP67	—	2, 5 or 10	PVC 3 x 0,12	37	M/50/EAN/*V
	10 ... 30	150	Closer	-40 ... +80	•	IP67	Plug M8 x 1	0,3	PVC 3 x 0,14	16	M/50/EAN/CP *1)

* Insert cable length; *1) Plug-in connector below; Color code: BK = black, BN = brown, BU = blue


Dimensions
**M/50/EAP/*V,
M/50/EAN/*V**

 Cable length L =
2, 5 or 10 m

**M/50/EAP/CP,
M/50/EAN/CP**

M/50/EAP/CC


- 1 Fixing screw
- 2 Color code
BK = black
BN = brown
BU = blue
- 3 Plug M8 x 1
- 4 Plug M12 x 1

QM/27/2/1 – Switch mounting brackets
Switch: M/50

Cyl. Ø	A	B	Weight (kg)	Model
32	9	7	0,010	QM/27/2/1
40	8	8	0,010	QM/27/2/1
50	7	5	0,010	QM/27/2/1
63	7	7	0,010	QM/27/2/1
80	7	4	0,010	QM/27/2/1
100	2	2	0,010	QM/27/2/1



- 1 Switch mounting bracket
- 2 Magnetically operated switch

Technical data - Reed switches - additional informations see data sheet N/en 4.3.021

Symbol	Voltage (V a.c.)	Voltage (V d.c.)	Current max. (A)	Function	Temperature (°C)	LED	Protection class	Features	Cable length (m)	Cable type	Weight (g)	Model
	10 ... 240	10 ... 240	1	Closer	-20 ... +80	•	IP66	—	2, 5 or 10	PVC 2 x 0,75	108 (2 m)	QM/32/*
	10 ... 240	10 ... 240	1	Closer	-20 ... +80	•	IP66	—	2	PUR 2 x 0,75	108	QM/32/2/PU
	10 ... 240	10 ... 240	2	Closer	-20 ... +150	—	IP66	High temperature	2, 5 or 10	Silicon 2 x 0,75	102 (2 m)	TQM/31/*
	10 ... 240	10 ... 240	1	Closer	-20 ... +80	•	IP66	Plug M12 x 1	—	—	15	QM/32/P *1)


Technical data - Solid state - additional informations see data sheet N/en 4.3.025

Symbol	Voltage (V d.c.)	Current max. (mA)	Function	Temperature (°C)	LED	Protection class	Features	Cable length (m)	Cable type	Weight (g)	Model
	10 ... 30	200	PNP	-20 ... +80	•	IP66	—	2, 5 or 10	PVC 3 x 0,5	102 (2 m)	QM/132/*
	10 ... 30	200	PNP	-20 ... +80	•	IP66	—	5	PUR 3 x 0,34		QM/132/5/PU
	10 ... 30	200	PNP	-20 ... +80	•	IP66	Plug M12 x 1			15	QM/132/P *1)


* Insert cable length
 *1) Plug-in connector see page below
 Color code: BK = black, BN = brown, BU = blue

Dimensions

TQM/31, QM/32, QM/132



QM/32/P, QM/132/P



1 LED (yellow)
 2 Plug M12 x 1
 Color code:
 BK = black
 BN = brown
 BU = blue

Accessories

Plug-in connector cable with nut




Outer cover	Cable length	Weight (kg)	Connector	Model
PVC 3 x 0,34	5 m	0,21	M12 x 1	M/P34692/5
PUR 3 x 0,34	5 m	0,21	M12 x 1	M/P34594/5

QM/31/000/22 – Switch mounting brackets


Switches: TQM/31, QM/32, QM/132

Cyl. Ø	A	B	Weight (kg)	Model
32	4,5	38	0,026	QM/31/032/22
40	5,5	43	0,026	QM/31/032/22
50	4,5	48	0,026	QM/31/032/22
63	4,5	53	0,026	QM/31/032/22
80	1,5	61	0,028	QM/31/080/22
100	0,5	68	0,028	QM/31/080/22




1 Switch mounting bracket
 2 Magnetically operated switch

Pneumatic proximity sensor - additional informations see data sheet N/en 4.3.061

Symbol	Operating pressure	Flow rate	Orifice size	Temperature	Optical indicator	Connections	Model
	2 ... 6 bar	40 l/min	2 mm	-15 ... +60°C	•	Pipes for 3 mm I/D tubing	QM/140

**QM/140/010/22 – Bracket with holding strap
Pneumatic switch: QM/140**

Cyl. Ø	A	B	Weight (kg)
32	31,5	18,5	0,020
40	30,5	18,5	0,020
50	31,5	18,5	0,020
63	29,5	18,5	0,020
80	30,5	18,5	0,020
100	30	18,5	0,020



- 1 Holding strap
- 2 Optical indicator
- 3 Pneumatic switch

Warning

These products are intended for use in industrial compressed air systems only. Do not use these products where values can exceed those listed under »**Technical features/data**«.

Before using these products with fluids other than those specified, for non-industrial applications, life-support systems, or other applications not within published specifications, consult NORGREN.

Through misuse, age, or malfunction, components used in fluid power systems can fail in various modes.

The system designer is warned to consider the failure modes of all component parts used in fluid power systems and to provide adequate safeguards to prevent personal injury or damage to equipment in the event of such failure.

System designers must provide a warning to end users in the system instructional manual if protection against a failure mode cannot be adequately provided.

System designers and end users are cautioned to review specific warnings found in instruction sheets packed and shipped with these products.